2 LB "B" SAFETY DATA SHEET

PRODUCT NAME: GHS SDS DATE: June 15, 2015

2 LB FOAM COMP "B"

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: TRANSPORTATION EMERGENCY CALL CHEMTREC:

 Multi-Tech Products
 800 424 9300

 41519 Cherry St
 INTERNATIONAL:

 Murrieta CA 92562
 703 527 3887

Phone: 951-834-9066

PRODUCTION IDENTIFICATION NUMBER: 2 LB Polyurethane Foam "B"

CHEMICAL FAMILY: POLYETHER POLYOL BLEND

RECOMMEDED USE: Pour foam/Injection – Composite Repair & Fabrication

SECTION 2: HAZARD INDENTIFICATION

GHS CLASSIFICATION

Skin irritation : Category 3

Eye irritation : Category 2

GHS Label Element Hazard pictograms



Signal word : Warning

Hazard statements : H315 May cause skin irritation.

: H320 May cause eye irritation. : H335 May cause respiratory irritation.

Precautionary Statements : P260 Do not breathe fume/gas/mist/vapors/spray.

: P280 Wear protective gloves/eye protection/face protection.

: P305+351+338 If in eyes, rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

: P302+352 If on skin, was with plenty of soap and water.

: P304+340 If inhaled, remove person to fresh air and keep comfortable for breathing.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL OR COMPONENT CAS NO. %BY WEIGHT

PROPRIETARY COMPONENT (Blend) Mixture 55-90 % GLYCOLS Mixture 0-10 %

*Occupational Exposure Limit(s), if available, are listed in Section 8.

SECTION 4: FIRST AID MEASURES

Eye Contact:Check for and remove any contact lenses. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: In case of contact, immediately wash skin with soap and plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

Inhalation: If excessive inhalation of vapor occurs, remove to fresh air. If breathing is difficult, qualified personnel may administer oxygen. Get medical attention immediately.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Notes to Physician: Symptomatic treatment and supportive therapy as indicated. Administer oxygen if necessary.

Following severe exposure the patient should be kept under medical review for at least 48 hours as delayed pulmonary edema may develop.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: >212°F Closed Cup

Auto Ignition Temp: Not available.

Flammable Limits: Not available.

Products of Combustion:

Thermal Decomposition products are toxic and may include oxides of carbon and nitrogen, amines, possibly other irritating gases.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Protective Clothing (Fire):

Splash goggles. Full suit. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product.

SECTION 6: ACCIDENTAL RELEASE MEASURES

For major spills call Chemtrec (800-424-9300) See Safety Data Sheet section 8 Personal Protective Equipment

Small Spill and Leak Absorb with an inert material and put the material in an appropriate waste disposal container.

Large Spill and Leak Corrosive liquid. Toxic liquid.

Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements of confined area; dike if needed. Eliminate all ignition sources. Call for assistance on disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the SDS and with local authorities.

SECTION 7: HANDLING AND STORAGE

Handling Do not ingest. Do not breathe vapor or mist. Keep container closed. Use only with adequate

ventilation.

Wash thoroughly after handling. Avoid contact with eyes, skin and clothing.

Storage Keep container tightly closed. Keep container in a cool, well-ventilated area.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Preventive Measures Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.

Engineering Controls Use local exhaust ventilation to maintain airborne concentrations bellow the TLV. Suitable respiratory equipment should be used in case of insufficient ventilation or where operational procedures demand it. For guidance on engineering control measures refer to publications such as the ACGIH current edition of 'Industrial Ventilation, a manual of Recommended Practice.'

Personal Protection

Eyes Chemical safety goggles. If there is a potential for splashing, use a full-face shield.

Body and Hands Full chemical suit. Gloves.

Respiratory Wear appropriate respirator when ventilation is inadequate.

Personal Protection in case of a Large Spill

Splash goggles. Full suit. Vapor respirator or a self-contained breathing apparatus. Boots. Gloves.

Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Product Name Exposure Limits

SECTION 9: PHYSICAL AHD CHEMICAL PROPERTIES

APPEARANCE AND ODOR
BOILING POINT (°F/°C)
MELTING POINT (°F/°C)
SPECIFIC GRAVITY (WATER = 1)
BULK DENSITY
pH OF UNDILUTED PRODUCT
VAPOR PRESSURE (MM Hg.)
VAPOR DENSITY (AIR-1)
VISCOSITY
PERCENT (%) VOC
SOLUBILITY IN WATER

Clear Slight Odor Not determined Not determined 1.12 kg/l 8.8 lb/gal Not determined Not determined >1

600 to 900 cps @ 25° C

0 Soluble

SECTION 10: STABILITY AND REACTIVITY

Stability and Reactivity This product is stable.

Conditions of Stability Avoid moisture to protect product quality.

Slightly reactive to reactive with oxidizing agents, alkalis.

Hazardous Decomposition Products

Thermal decomposition products are toxic and may include oxides of carbon and nitrogen, amines, possibly other irritating gases.

Hazardous Polymerization Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

No applicable data for this section.

SECTION 12: ECOLOGICAL INFORMATION

No applicable data for this section.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Information Incinerate or landfill in a licensed facility. Do not discharge into waterways of sewer systems.

Container Disposal: Steel drums must be emptied (as defined by RCRA, Section 261.7 or state regulations that may be more stringent) and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approve landfill. Drums destined for scrap dealer of landfill must be punctured or crushed to prevent reuse.

Material for disposal should be placed in appropriated sealed containers to avoid potential human and environmental exposure. It is the responsibility of the generator to comply with all federal, state, provincial and local laws and regulations. We recommend that you contact an appropriate waste disposal contractor and environmental agency for relevant laws and regulations. Under the US, Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user of the product to determined at the time of disposal, whether the product meets relevant waste classification and to assure proper disposal.

SECTION 14: TRANSPORT INFORMATION

Transportation Emergency Number 1-800-424-9300 (CHEMTREC).

DOT Classification Non Regulated TDG Classification Non Regulated IMO/IMDG Classification Non Regulated ICAO/IATA Classification Non Regulated Non Regulated

SECTION 15: REGULATORY INFORMATION

U.S. Federal Regulations

This material is classified as hazardous under OSHA Hazard Communication Standard (29 CFR 1910.1200).

HCS Classification

Class: Corrosive material

TSCA 8(b) inventory: All ingredients Listed.

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act):

Any spill or release above the RC must be reported to the National Response Center (800-424-8802)

State Regulations California prop 65: No ingredients listed.

Canadian Regulations

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and this SDS (Safety Data Sheet) contains all the information required by the CPR.

WHMIS (Canada) Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2B: Material causing other toxic effects (Toxic).

CEPA DSL/NDSL Not all Ingredients Listed.

SECTION 16: OTHER INFORMATION

Causes respiratory tract, eye and skin burns.

Harmful if inhaled.

May be harmful if swallowed.

Contains material, which may cause birth defects based on animal data.

Hazardous Material Information System (U.S.A.) National Fire Protection Association (U.S.A.)

Health:1Health:1Fire Hazard:1Fire Hazard:1Reactivity:0Reactivity:0

Notice to Reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONSAND THE SUITABILITY OF ANY PRIDUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZAEDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity, and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

We disclaim liability for damage or injury incurring directly or indirectly from the use of this product.