

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

SECTION 1. IDENTIFICATION

Product name : HI-POINT 90

Manufacturer or supplier's details

Company name of supplier : JV ENT, LLC (**DBA:** Multi-Tech Products)

Address : 1177 N. Red Gum Street
Anaheim, CA 92806 USA

Telephone : +1-800-218-2066

Telefax : +1-657-254-5344

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300
CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person responsible for the SDS : orders@multitechproducts.com

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 4

Organic peroxides : Type D

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin corrosion : Category 1B

Serious eye damage : Category 1

Reproductive toxicity : Category 2

Short-term (acute) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Hazard Statements : H227 Combustible liquid.
H242 Heating may cause a fire.
H302 + H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.
H361d Suspected of damaging the unborn child.
H401 Toxic to aquatic life.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.
P234 Keep only in original container.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P405 Store locked up.
P410 Protect from sunlight.
P411 + P235 Store at temperatures not exceeding < 100 °F/ < 38 °C. Keep cool.
P420 Store away from other materials.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

Version 2.0 Revision Date: 12/04/2019 SDS Number: MTP120419 Date of last issue: 10/19/2018
 Date of first issue: 09/21/2016

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Organic Peroxide
 Liquid mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
dimethyl phthalate	131-11-3	>= 40 - < 45
2-Butanone, peroxide	1338-23-4	>= 30 - < 35
Trimethylpentanediol isobutyrate	6846-50-0	>= 20 - < 25
Butanone	78-93-3	>= 1 - < 5
Hydrogen peroxide	7722-84-1	>= 1 - < 2.5

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this material safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
 Symptoms of poisoning may appear several hours later.
 Call a physician immediately.

If inhaled : Call a physician or poison control center immediately.
 If unconscious, place in recovery position and seek medical advice.
 Keep respiratory tract clear.
 Call a physician immediately.
 If breathed in, move person into fresh air.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Wash contaminated clothing before re-use.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
 If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
 In the case of contact with eyes, rinse immediately with plenty

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

	of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Keep respiratory tract clear. Do NOT induce vomiting. Call a physician immediately. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: Harmful if swallowed or if inhaled. Causes serious eye damage. Suspected of damaging the unborn child. Causes severe burns.
Protection of first-aiders	: First Aid responders should pay attention to self-protection and use the recommended protective clothing
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray jet Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire fighting	: Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite. Flash back possible over considerable distance. Vapors may form explosive mixtures with air. Cool closed containers exposed to fire with water spray.
Specific extinguishing methods	: Do not use a solid water stream as it may scatter and spread fire. Remove undamaged containers from fire area if it is safe to do so. Use water spray to cool unopened containers.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
 Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Remove all sources of ignition.
 Follow safe handling advice and personal protective equipment recommendations.
 Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
 Never return spills in original containers for re-use.
 Treat recovered material as described in the section "Disposal considerations".

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contact with incompatible substances can cause decomposition at or below SADT.
 Clear spills immediately.
 Suppress (knock down) gases/vapors/mists with a water spray jet.
 To clean the floor and all objects contaminated by this material, use plenty of water.
 Soak up with inert absorbent material.
 Isolate waste and do not reuse.
 Non-sparking tools should be used.
 Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
 Use only explosion-proof equipment.
 Keep away from combustible material.

Advice on safe handling : Do not swallow.
 Do not breathe vapors/dust.
 Avoid contact with skin and eyes.
 Avoid formation of aerosol.
 Take precautionary measures against static discharges.
 Never return any product to the container from which it was originally removed.

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Provide sufficient air exchange and/or exhaust in work rooms.
Avoid confinement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Smoking, eating and drinking should be prohibited in the application area.
Wash thoroughly after handling.
For personal protection see section 8.
Protect from contamination.

Conditions for safe storage : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.
Electrical installations / working materials must comply with the technological safety standards.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Store in original container.
Keep containers tightly closed in a cool, well-ventilated place.
Store in accordance with the particular national regulations.

Materials to avoid : Keep away from strong acids, bases, heavy metal salts and other reducing substances.

Recommended storage temperature : < 100 °F

< 38 °C

Further information on storage stability : No decomposition if stored normally.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m ³	ACGIH
		TWA	5 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	OSHA P0
2-Butanone, peroxide	1338-23-4	C	0.2 ppm	ACGIH
		C	0.2 ppm 1.5 mg/m ³	NIOSH REL
		C	0.7 ppm 5 mg/m ³	OSHA P0
Butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m ³	NIOSH REL
		ST	300 ppm 885 mg/m ³	NIOSH REL
		TWA	200 ppm 590 mg/m ³	OSHA Z-1

Safety Data Sheet

Version 2.0 Revision Date: 12/04/2019 SDS Number: MTP120419 Date of last issue: 10/19/2018
Date of first issue: 09/21/2016

		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0
Hydrogen peroxide	7722-84-1	TWA	1 ppm	ACGIH
		TWA	1 ppm 1.4 mg/m3	NIOSH REL
		TWA	1 ppm 1.4 mg/m3	OSHA Z-1
		TWA	1 ppm 1.4 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Hand protection

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0.5 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove Wash hands before breaks and at the end of workday.

Eye protection : Tightly fitting safety goggles
Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure

Version 2.0	Revision Date: 12/04/2019	SDS Number: MTP120419	Date of last issue: 10/19/2018 Date of first issue: 09/21/2016
----------------	------------------------------	--------------------------	---

potential.

Hygiene measures : Keep away from food and drink.
 When using do not eat or drink.
 When using do not smoke.
 Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	colorless
Odor	:	slight
pH	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	Decomposition: Decomposes below the boiling point.
Flash point	:	76 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	> 1
Density	:	1.1 g/cm3
Solubility(ies) Water solubility	:	soluble
Partition coefficient: n-octanol/water	:	No data available
Self-Accelerating decomposition temperature (SADT)	:	60 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Version 2.0	Revision Date: 12/04/2019	SDS Number: MTP120419	Date of last issue: 10/19/2018 Date of first issue: 09/21/2016
----------------	------------------------------	--------------------------	---

Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	not determined
Oxidizing properties	:	The substance or mixture is not classified as oxidizing. Organic peroxide

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Vapors may form explosive mixture with air.
Conditions to avoid	:	Protect from contamination. Contact with incompatible substances can cause decomposition at or below SADT. Heat, flames and sparks. Avoid confinement.
Incompatible materials	:	Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents
Hazardous decomposition products	:	Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 1,431 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 4.29 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

Components:

dimethyl phthalate:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	(Rat): > 10.4 mg/l

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Exposure time: 6 h
 Test atmosphere: vapor
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 12,000 mg/kg

2-Butanone, peroxide:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
 Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 1.5 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: Expert judgment
 Assessment: The component/mixture is moderately toxic after short term inhalation.
 Remarks: Based on data from similar materials

Acute dermal toxicity : Acute toxicity estimate: 2,500 mg/kg
 Method: Expert judgment

Trimethylpentanediol isobutyrate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: Expert judgment
 Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LCLo (Rat): > 0.12 mg/l
 Exposure time: 6 h
 Test atmosphere: dust/mist
 Method: Expert judgment
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg
 Method: Expert judgment
 Assessment: The substance or mixture has no acute dermal toxicity

Butanone:

Acute oral toxicity : LD50 (Rat): 2,193 mg/kg
 Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
 Method: OECD Test Guideline 402

Hydrogen peroxide:

Acute oral toxicity : LD50 (Rat, male): 1,026 mg/kg
 Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.17 mg/l

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 6,500 mg/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks : Extremely corrosive and destructive to tissue.

Components:

dimethyl phthalate:

Species : Rabbit
Method : Draize Test
Result : No skin irritation

2-Butanone, peroxide:

Species : Rabbit
Result : Causes burns.

Trimethylpentanediol isobutyrate:

Species : Guinea pig
Exposure time : 24 h
Result : No skin irritation
Remarks : Based on available data, the classification criteria are not met.

Butanone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Hydrogen peroxide:

Result : Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks : May cause irreversible eye damage.

Components:

dimethyl phthalate:

Species : Rabbit

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Result	: No eye irritation
Method	: OECD Test Guideline 405

2-Butanone, peroxide:

Result	: Irreversible effects on the eye
--------	-----------------------------------

Trimethylpentanediol isobutyrate:

Species	: Rabbit
Result	: No eye irritation

Butanone:

Species	: Rabbit
Result	: Eye irritation
Method	: OECD Test Guideline 405

Hydrogen peroxide:

Result	: Irreversible effects on the eye
--------	-----------------------------------

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

dimethyl phthalate:

Species	: Mouse
Method	: OECD Test Guideline 429
Result	: Does not cause skin sensitization.

2-Butanone, peroxide:

Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitization.

Assessment	: Harmful if swallowed., Harmful if inhaled.
------------	--

Trimethylpentanediol isobutyrate:

Species	: Guinea pig
Result	: Does not cause skin sensitization.

Butanone:

Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Does not cause skin sensitization.

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Germ cell mutagenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Genotoxicity in vitro	:	Method: OECD Test Guideline 471 Result: negative
		Method: OECD Test Guideline 473 Result: negative
		Method: OECD Test Guideline 476 Result: positive
Genotoxicity in vivo	:	Test Type: Chromosomal aberration Species: Rat Application Route: Intraperitoneal Result: negative
		Test Type: Micronucleus test Species: Mouse Application Route: Intraperitoneal injection Result: negative

2-Butanone, peroxide:

Genotoxicity in vitro	:	Method: OECD Test Guideline 473 Result: negative
		Method: OECD Test Guideline 471 Result: negative
		Method: OECD Test Guideline 476 Result: negative

Trimethylpentanediol isobutyrate:

Genotoxicity in vitro	:	Method: OECD Test Guideline 476 Result: negative
		Test Type: Ames test Result: negative
		Method: OECD Test Guideline 473 Result: negative

Butanone:

Genotoxicity in vitro	:	Method: OECD Test Guideline 471 Result: negative
		Method: OECD Test Guideline 476 Result: negative
		Method: OECD Test Guideline 473

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Result: negative

Genotoxicity in vivo : Species: Mouse
 Application Route: Intraperitoneal
 Method: OECD Test Guideline 474
 Result: negative

Hydrogen peroxide:

Genotoxicity in vitro : Test Type: Ames test
 Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
 cytogenetic assay)
 Species: Mouse
 Result: negative

Carcinogenicity

Not classified based on available information.

Components:

dimethyl phthalate:

Species : Rat
 Application Route : Skin contact
 Method : OECD Test Guideline 451
 Result : negative
 Remarks : Based on data from similar materials

2-Butanone, peroxide:

Remarks : This information is not available.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

dimethyl phthalate:

Effects on fertility : Species: Rat
 Application Route: oral (gavage)
 Method: OECD Test Guideline 440
 Result: negative

Effects on fetal development : Species: Rat
 Application Route: Ingestion

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

General Toxicity Maternal: NOAEL: 840 mg/kg body weight
Developmental Toxicity: NOAEL: 3,570 mg/kg body weight
Method: OECD Test Guideline 414

2-Butanone, peroxide:

Effects on fertility : Species: Rat
Application Route: oral (gavage)
General Toxicity Parent: NOAEL: 50 mg/kg body weight
Method: OECD Test Guideline 421
Result: negative

Trimethylpentanediol isobutyrate:

Effects on fetal development : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

Butanone:

Effects on fertility : Species: Rat
Application Route: oral (drinking water)
General Toxicity Parent: NOAEL: 10,000 mg/l
General Toxicity F1: NOAEL: 10,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Species: Rat
Application Route: oral (drinking water)
General Toxicity Parent: LOAEL: 20,000 mg/l
Method: OECD Test Guideline 416
Remarks: Based on data from similar materials

Effects on fetal development : Species: Rat
Application Route: Inhalation
General Toxicity Maternal: NOAEC: ca. 1,002 mg/kg body weight
Teratogenicity: NOAEC Parent: ca. 1,002 mg/kg body weight
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

Not classified based on available information.

Components:

Butanone:

Assessment : May cause drowsiness or dizziness.

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Hydrogen peroxide:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity**Components:****dimethyl phthalate:**

Species	: Rat
NOAEL	: 770 mg/kg
Application Route	: Oral
Exposure time	: 16 w
Method	: OECD Test Guideline 408

2-Butanone, peroxide:

Species	: Rat
NOAEL	: 200 mg/kg
Application Route	: oral (gavage)
Exposure time	: 28 d
Method	: OECD Test Guideline 407

Repeated dose toxicity - Assessment : Harmful if swallowed., Harmful if inhaled.

Hydrogen peroxide:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 90 d
Symptoms	: No adverse effects.

Aspiration toxicity

Not classified based on available information.

Components:**dimethyl phthalate:**

No aspiration toxicity classification

Trimethylpentanediol isobutyrate:

Not classified due to data which are conclusive although insufficient for classification.

Further information**Product:**

Remarks : No data available

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Components:

dimethyl phthalate:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

dimethyl phthalate:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 39 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): > 52 mg/l Exposure time: 48 h
Toxicity to algae	:	EC50 (Desmodesmus subspicatus (green algae)): 260 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Oncorhynchus mykiss (rainbow trout)): 11 mg/l Exposure time: 102 d Method: OECD Test Guideline 210 LOEC (Oncorhynchus mykiss (rainbow trout)): 24 mg/l Exposure time: 102 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 9.6 mg/l Exposure time: 21 d LOEC (Daphnia magna (Water flea)): 23 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC50: 4,100 mg/l Exposure time: 0.5 h Method: OECD Test Guideline 209

Ecotoxicology Assessment

Acute aquatic toxicity	:	This product has no known ecotoxicological effects.
Chronic aquatic toxicity	:	This product has no known ecotoxicological effects.

2-Butanone, peroxide:

Toxicity to fish	:	LC50 (Poecilia reticulata (guppy)): 44.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 NOEC (Poecilia reticulata (guppy)): 18 mg/l Exposure time: 96 h
------------------	---	---

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 26.7 mg/l
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 5.6 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2.1 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l
 Exposure time: 0.5 h
 Method: OECD Test Guideline 209

Trimethylpentanediol isobutyrate:

Toxicity to fish : NOEC (Fish): >= 6 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia): >= 1.46 mg/l
 Exposure time: 48 h
 NOEC (Daphnia): 0.7 mg/l
 Exposure time: 21 d

Toxicity to algae : EC50 (Chlorella pyrenoidosa): > 7.49 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : LOEC (Daphnia magna (Water flea)): 0.7 mg/l
 Exposure time: 21 d

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 308 mg/l

Version 2.0	Revision Date: 12/04/2019	SDS Number: MTP120419	Date of last issue: 10/19/2018 Date of first issue: 09/21/2016
----------------	------------------------------	--------------------------	---

aquatic invertebrates	Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): 2,029 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to microorganisms	: NOEC (Pseudomonas putida): 1,150 mg/l Exposure time: 16 h Method: DIN 38 412 Part 8

Hydrogen peroxide:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 16.4 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: LC50 (Daphnia pulex (Water flea)): 2.4 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Skeletonema costatum (marine diatom)): 1.38 mg/l Exposure time: 72 h NOEC (Skeletonema costatum (marine diatom)): 0.63 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.63 mg/l Exposure time: 21 d

Persistence and degradability

Components:

dimethyl phthalate:

Biodegradability	: Result: Readily biodegradable. Method: OECD Test Guideline 301E
------------------	--

2-Butanone, peroxide:

Biodegradability	: Result: Readily biodegradable. Method: OECD Test Guideline 301D
------------------	--

Trimethylpentanediol isobutyrate:

Biodegradability	: Result: rapidly biodegradable Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

Butanone:

Biodegradability	: Result: Readily biodegradable. Method: OECD Test Guideline 301D
------------------	--

Hydrogen peroxide:

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Components:

dimethyl phthalate:

Bioaccumulation : Bioconcentration factor (BCF): 57
 Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 1.54

2-Butanone, peroxide:

Partition coefficient: n-octanol/water : log Pow: < 0.3 (25 °C / 25 °C)

Trimethylpentanediol isobutyrate:

Bioaccumulation : Species: Fish
 Bioconcentration factor (BCF): 1.95

Partition coefficient: n-octanol/water : log Pow: 4.91 (25 °C / 25 °C)

Butanone:

Partition coefficient: n-octanol/water : log Pow: 0.3 (40 °C / 40 °C)

Hydrogen peroxide:

Partition coefficient: n-octanol/water : log Pow: -1.57
 Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
 Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Toxic to aquatic life.

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Components:

dimethyl phthalate:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.
 Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3105
 Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
 (METHYL ETHYL KETONE PEROXIDE(S))
 Class : 5.2
 Packing group : Not assigned by regulation
 Labels : 5.2

IATA-DGR

UN/ID No. : UN 3105
 Proper shipping name : Organic peroxide type D, liquid
 (Methyl ethyl ketone peroxide(s))
 Class : 5.2
 Packing group : Not assigned by regulation
 Labels : Organic Peroxides, Keep Away From Heat
 Packing instruction (cargo aircraft) : 570
 Packing instruction (passenger aircraft) : 570

IMDG-Code

UN number : UN 3105
 Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
 (METHYL ETHYL KETONE PEROXIDE(S))
 Class : 5.2
 Packing group : Not assigned by regulation
 Labels : 5.2
 EmS Code : F-J, S-R

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number	: UN 3105
Proper shipping name	: Organic peroxide type D, liquid (Methyl ethyl ketone peroxide(s), <=45%)
Class	: 5.2
Packing group	: Not assigned by regulation
Labels	: ORGANIC PEROXIDE
ERG Code	: 145
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2-Butanone, peroxide	1338-23-4	10	29

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Hydrogen peroxide	7722-84-1	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)
Hydrogen peroxide	7722-84-1	1000

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Organic peroxides
 Acute toxicity (any route of exposure)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Reproductive toxicity

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Version 2.0	Revision Date: 12/04/2019	SDS Number: MTP120419	Date of last issue: 10/19/2018 Date of first issue: 09/21/2016
----------------	------------------------------	--------------------------	---

dimethyl
phthalate 131-11-3

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

dimethyl phthalate 131-11-3

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Butanone 78-93-3

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

dimethyl phthalate 131-11-3

Maine Chemicals of High Concern

This product does not contain any chemicals that are listed as Maine Chemicals of High Concern.

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

DSL (CA)	: All components of this product are on the Canadian DSL
AICS (AU)	: On the inventory, or in compliance with the inventory
ENCS (JP)	: On the inventory, or in compliance with the inventory
ISHL (JP)	: On the inventory, or in compliance with the inventory
KECI (KR)	: On the inventory, or in compliance with the inventory
PICCS (PH)	: On the inventory, or in compliance with the inventory
IECSC (CN)	: On the inventory, or in compliance with the inventory
TCSI (TW)	: On the inventory, or in compliance with the inventory
TSCA (US)	: On TSCA Inventory

TSCA list

No substances are subject to a Significant New Use Rule.

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amend-

Version	Revision Date:	SDS Number:	Date of last issue: 10/19/2018
2.0	12/04/2019	MTP120419	Date of first issue: 09/21/2016

ments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues.

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 12/04/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.