

EXCELLENCE IN SURFACE REPAIR PRODUCTS

# SAFETY DATA SHEET

Former Date: 02/15/2015

Revision Date: 12/20/2020

Version: 1

#### 1. Identification

**Rubbing Compound Product identifier** 

None. Other means of identification Polish. Recommended use None known. Recommended restrictions

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier JV ENT, LLC (DBA: Multi-Tech Products)

**Address** 1177 N. Red Gum Street

Anaheim, CA 92806 United States

Telephone: (800) 218-2066

CHEMTREC: (800) 424-9300 **Emergency** 

CHEMTREC International: 00 1-703-527-3887

# 2. Hazard(s) identification

**Physical hazards** Flammable liquids Skin Category 4

**Health hazards** corrosion/irritation Category 1

> Serious eye damage/eye irritation Category 1 Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2 (lungs)

exposure (inhalation)

Not classified.

**OSHA** defined hazards

Label elements



Signal word Danger

**Hazard statement** Combustible liquid. Causes severe skin burns and eye damage. May cause cancer by inhalation.

May cause respiratory irritation. May cause damage to organs (lungs) through prolonged or

repeated exposure by inhalation.

**Precautionary statement** 

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

> and understood. Keep away from flames and hot surfaces-No smoking. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear

protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. In case of fire: Use water fog, alcohol

resistant foam, dry chemical powder, carbon dioxide to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

**Rubbing Compound** SDS US

Date: 12/20/2020

1/8

# 3. Composition/information on ingredients

#### **Mixtures**

CAS number	%	
7732-18-5	35 - 40	
64742-96-7	30 - 35	
14808-60-7	15 - 20	
61790-12-3	5 - 10	
141-43-5	1 - 5	
8002-09-3	1 - 5	
	7732-18-5 64742-96-7 14808-60-7 61790-12-3 141-43-5	

**Composition comments** 

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes permanent skin damage (scarring). Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. May cause respiratory irritation. Coughing. Wheezing. Difficulty in breathing. May cause damage to organs (lungs) through prolonged or repeated exposure by inhalation. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Prolonged exposure may cause chronic

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

effects.

Rubbing Compound SDS US

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

. . .

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

# Environmental precautions

7. Handling and storage Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

**Occupational exposure limits** 

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
2-Aminoethanol (CAS 141-43-5)	PEL	6 mg/m3
US OSHA Table 7-3 (29 CFR 1910 1000)		3 ppm

UJ.	COLIA	Iable	<u> </u>	29 01	11 13	10.1000

Components	Туре	Value	Form	
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.	
		0.1 mg/m3	Respirable.	
		2.4 mppcf	Respirable.	

## **US. ACGIH Threshold Limit Values**

Components	Туре	Value	Form
2-Aminoethanol (CAS 141-43-5)	STEL	6 ppm	
·	TWA	3 ppm	
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Solvent Naphtha (petroleum), Heavy Aliphatic (CAS 64742-96-7)	TWA	200 mg/m3	Non-aerosol.

#### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	Form
2-Aminoethanol (CAS	STEL	15 mg/m3	
141-43-5)		6 ppm	
	TWA	8 mg/m3	
		3 ppm	

Rubbing Compound SDS US

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Solvent Naphtha (petroleum), Heavy Aliphatic (CAS 64742-96-7)	TWA	100 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

**US ACGIH Threshold Limit Values: Skin designation** 

Solvent Naphtha (petroleum), Heavy Aliphatic (CAS Can be absorbed through the skin.

64742-96-7)

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear chemical goggles and face shield.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves.

Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other Wear chemical-resistant gloves, footwear and protective clothing appropriate for risk of exposure.

Contact glove manufacturer for specific information.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor

cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Cream.
Color Not available.

Odor Not available.

Odor threshold Not available.

Ph Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point > 140.0 °F (> 60.0 °C) (Estimated)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.
Flammability limit - upper (%) Not available.

Rubbing Compound SDS US

Explosive limit - lower (%)
Explosive limit - upper (%)

Vapor pressure
Vapor density

Relative density

Not available.

Not available.

Not available.

Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.DecompositiontemperatureNot available.ViscosityNot available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizers, strong acids, and strong bases. Amines.

Hazardous decomposition

products

Thermal decomposition of this product can generate carbon monoxide and carbon dioxide.

Nitrogen oxides.

# 11. Toxicological information

## Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

irritation to the respiratory system.

Skin contactCauses severe skin burns.Eye contactCauses serious eye damage.IngestionCauses digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes permanent skin damage (scarring). Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. May cause respiratory irritation. Coughing. Wheezing. Difficulty in breathing. May cause damage to organs (lungs) through prolonged or repeated exposure by inhalation. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Prolonged exposure may cause chronic effects.

## Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation Serious

eye damage/eye irritation

Causes severe skin burns.
Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Skin

Germ cell mutagenicity

Date: 12/20/2020

Not a respiratory sensitizer.

sensitization This product is not expected to cause skin sensitization.

Sensitization

No data available to indicate product or any components present at greater than

0.1% are mutagenic or genotoxic.

Carcinogenicity May cause cancer.

Rubbing Compound SDS US

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

**NTP Report on Carcinogens** 

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lungs) through prolonged or repeated exposure by inhalation.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**Further information** Symptoms may be delayed.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient n-octanol / water (log Kow)

2-Aminoethanol (CAS 141-43-5) -1.31

Mobility in soil No data available for this product.

Other adverse effects

Substantial amounts of the product may lead to a local change in acidity in small water systems

which may have adverse effects on aquatic organisms.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN2491

UN proper shipping name Ethanolamine solutions

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group III
Environmental hazards

Marine pollutant No

warine pollutarit No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T4, TP1

Packaging exceptions154Packaging non bulk203Packaging bulk241

Rubbing Compound SDS US

**IATA** 

UN number UN2491

UN proper shipping name Ethanolamine solution

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group III
Environmental hazards No
ERG Code 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN number UN2491

UN proper shipping name ETHANOLAMINE SOLUTION

Transport hazard class(es)

Class 8
Subsidiary risk Label(s) 8
Packing group III
Environmental hazards

Marine pollutant No mS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not applicable.

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Rubbing Compound SDS US

Date: 12/20/2020 7 / 8

#### **US state regulations**

#### **US. Massachusetts RTK - Substance List**

2-Aminoethanol (CAS 141-43-5)

Quartz (CAS 14808-60-7)

Solvent Naphtha (petroleum), Heavy Aliphatic (CAS 64742-96-7)

## US. New Jersey Worker and Community Right-to-Know Act

2-Aminoethanol (CAS 141-43-5)

Pine Oil (CAS 8002-09-3)

Quartz (CAS 14808-60-7)

Solvent Naphtha (petroleum), Heavy Aliphatic (CAS 64742-96-7)

#### US. Pennsylvania Worker and Community Right-to-Know Law

2-Aminoethanol (CAS 141-43-5)

Quartz (CAS 14808-60-7)

Solvent Naphtha (petroleum), Heavy Aliphatic (CAS 64742-96-7)

#### US. Rhode Island RTK

Not regulated.

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

# US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

# 16. Other information, including date of preparation or last revision

## **GHS SDS**

**Date** June 1, 2015

United States & Puerto Rico

#### NFPA ratings



# Disclaimer

Multi-Tech Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Rubbing Compound SDS US

Date: 12/20/2020

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).